

An aerial photograph of three offshore wind turbines in the ocean. The turbines are white with yellow mooring systems. The sky is blue with scattered white clouds. The water is a deep blue. The turbines are arranged in a line, with the closest one on the right and two others further out to sea.

# Design of Deep-Water Mooring Systems, Suspended Power Cables, and Array Layout

IEA Wind Task 49 Deep Water Design Team  
January 15<sup>th</sup>, 2025

# Task 49 Deep Water Design Team



Task 49 Integrated Design of Floating Wind Arrays  
Work Package 2: Developing Reference Array Designs

## Deep Water Design Team:

Ericka Lozon<sup>1</sup>, Vishnu R.N. Rajasree<sup>2</sup>, Matthew Hall<sup>1</sup>, Michel Castagne<sup>3</sup>, Alice Nassor<sup>3</sup>, Yuksel Rudy Alkarem<sup>1</sup>, Michael Biglu<sup>1</sup>, Junho Lee<sup>4</sup>, Yann Poirette<sup>3</sup>, Mohammad Youssef Mahfouz<sup>5</sup>, Leah Sirkis<sup>1</sup>

<sup>1</sup> National Renewable Energy Laboratory (NREL)

<sup>2</sup> Norwegian University of Science and Technology (NTNU)

<sup>3</sup> IFP Energies Nouvelles (IFPEN)


<sup>4</sup> Deep Anchor Solutions Inc.

<sup>5</sup> University of Stuttgart

And ideas, feedback, and advice from many other Task 49 Contributors!

# Design Basis

IEA Task 49 design basis document outlines assumptions




Initial Mooring Configuration

<b>Scenario</b>	<b>Deep (800 m)</b>
<b>Key Features</b>	Deep water challenges and solutions
<b>Design Variants</b>	<b>V1:</b> uniform <i>Optional variants:</i> <b>V2:</b> shared mooring option <b>V3:</b> TLP option
<b>Array Layout</b>	Rectangular
<b>Platform and Turbine Type</b>	VoltturnUS-S semi-submersible and IEA 15 MW
<b>Mooring Type</b>	Taut (chain-polyester-chain)
<b>Mooring Configuration</b>	3-line mooring system, uniformly distributed headings
<b>Anchors</b>	Suction pile
<b>Dynamic Cables</b>	Catenary or lazy wave, fully suspended


# Site Conditions

- 800 m uniform water depth
- Extreme and fatigue load cases

Wind rose at the Humboldt site



DLC	1.6	6.1	SLC
Wind speed (m/s)	10.59	39.44	42.97
TI	0.06	0.05	0.05
Shear	0.14	0.11	0.11
Wave height (m)	10.5	11.8	13.7
Wave period (s)	18.7	19.8	21.4
Current speed (m/s)	0.92	1.28	1.44
Safety factor	2	2	1.05



# Mooring Design




Key constraints:

- Tension safety factor
- Fatigue
- **Slack line events**

Three design paths to limit slacking:

	High pretension	Buoy	Clump weight
Anchoring radius (m)	1400	1400	1400
Chain diameter (mm)	135	135	135
Polyester diameter (mm)	210	183	200
Buoy (m <sup>3</sup> )	0	27	0
Weight (t)	0	0	40
Pretension (kN)	3380	1600	1900 kN*

\*Pretension without clump weight 900 kN



# Mooring Design


Mooring fatigue damage varies widely

At different orientations:

- 2.5x increase depending on mooring orientation relative to wind

Wake effects (incr TI and deficit):

- 5x increase with 5D spacing
- 4x increase with 8D spacing
- **Assumed 9.6D spacing based on layout design**



	Mooring fatigue damage
No wake effects	0.11
5D spacing	0.49
8D spacing	0.40
Allowable	0.33

# Anchor Design

Sediment type: mostly mud with rock areas

Optimize the suction anchor dimensions, using plastic limit analysis (PLA)

Key considerations:

- Geotechnical efficiency
- Suction installability
- Cost-effectiveness
- Carbon impact



Suction anchor

OPTIMIZED SUCTION ANCHOR DESIGN AND ITS SUCTION INSTALLABILITY

	Case 2	Case 3	Case 4	Case 5	Case 6	Case 7
Aspect ratio ( $L/D$ )	4	5	6	7	8	9
Diameter ( $D$ , m)	3.90	3.53	3.23	3.0	2.82	2.65
Length ( $L$ , m)	15.6	17.7	19.4	21.0	22.6	23.9
Weight* ( $W$ , ton)	78.3	72.0	65.9	61.3	55.3	54.0
Vertical load ( $V$ , MN) (Green if $V > 5.8$ MN)	6.7	6.8	6.7	6.7	6.8	6.8
Inclined load ( $I$ , MN) (Green if $I > 10.7$ MN)	13.0	13.4	13.3	13.4	13.5	13.5
Horizontal load ( $H$ , MN) (Green if $H > 11.7$ MN)	13.5	15.2	16.5	17.7	19	19.7
<b>Feasibility Check</b>						
Geotechnical efficiency ( $=V/W$ )	8.9	9.8	10.6	11.3	12.8	13.1
Geotechnical efficiency ( $=H/W$ )	17.9	21.9	26.0	29.9	35.6	37.8
Suction installability $F.S.$	3.08	2.4	2.04	1.8	1.63	1.48
$F.S. > 1.5$	Feasible	Feasible	Feasible	Could be feasible	Could be feasible	Not feasible

# Suspended Cable Design

## Key Constraint – Tension


### Design challenge: Marine growth

– Following DNV GL guidelines:


- 100 mm growth to 50 m depth
- 50 mm growth below 50 m depth

– Changed assumptions to 0 marine growth below 170 m depth

Without Marine Growth



With Marine Growth







# Suspended Cable Design

## Design challenge: Current



- Current flow perpendicular to the cable is most challenging
- Tensions are highly sensitive to current profile with depth



# Array Layout

Layout goals to reduce mooring fatigue and wake losses:

- Increase turbine spacing in predominant wind direction
- Avoid mooring lines headed directly upwind




$D = 240 \text{ m}$


$$\begin{aligned} S'_x &= 6.36D \\ S'_y &= 7.09D \\ \alpha &= 290^\circ \\ \gamma &= \pm 30^\circ \end{aligned}$$

# Cable Routing

- Three conductor sizes
  - 300, 630, and 1000 mm<sup>2</sup>
- OSS fits within gridded layout
- Lazy-wave and suspended configurations




Lazy wave



# Conclusions and Next Steps

- The finalized deep water array design will be made publicly available
- Currently working on an LCOE analysis
- Task 49 shallow and intermediate depth designs are also in progress



# Questions?


---

[Ericka.Lozon@nrel.gov](mailto:Ericka.Lozon@nrel.gov)


This work was authored in part by the National Renewable Energy Laboratory, operated by Alliance for Sustainable Energy, LLC, for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. Funding provided by the U.S. Department of Energy Office of Energy Efficiency and Renewable Energy Wind Energy Technologies Office. The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government. The U.S. Government retains and the publisher, by accepting the article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for U.S. Government purposes.

# Fatigue Bins


Fatigue bins generated using a maximum dissimilarity algorithm



# Anchor Design



Sediment type: mostly “mud” with localized hard rock and outcrops (BOEM. 2023)



Suction installability analysis